

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Product name	: Nordlub Kompressorenöl VDL 150
Product code	: 4209
Type of product	: NORDLUB
Product group	: Blend
Other means of identification	: Art.-Nr.: 17004

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	: Industrial use, Professional use, Consumer use
Industrial/Professional use spec	: Non-dispersive use Used in closed systems
Function or use category	: Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

NORDLUB Deutschland GmbH
Lange Str. 49
D-21614 Buxtehude - Deutschland / Germany
T +49 (0)4161 / 55 905 - 0 - F +49 (0)4161 / 55 905 - 29
info@nordlub.de - www.nordlub.de

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word (CLP)	: -
Hazard statements (CLP)	: H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P273 - Avoid release to the environment. P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.
EUH-statements	: EUH208 - Contains Aryl amine. May produce an allergic reaction.

2.3. Other hazards

No additional information available

Nordlub Kompressorenöl VDL 150

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments : The mineral oils in the product contain < 3% DMSO extract (IP 346)

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Solvent naphtha (petroleum), heavy aromatic	(CAS-No.) 64742-94-5 (EC-No.) 265-198-5 (EC Index-No.) 649-424-00-3	0,1 – 0,99	STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
alkylphenol	(CAS-No.) 128-39-2 (EC-No.) 204-884-0 (REACH-no) 01-2119490822-33	0,1 – 0,49	Skin Irrit. 2, H315 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Aryl amine	(CAS-No.) 90-30-2 (EC-No.) 201-983-0	0,1 – 0,24	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Naphthalene	(CAS-No.) 91-20-3 (EC-No.) 202-049-5 (EC Index-No.) 601-052-00-2	0,1 – 0,24	Acute Tox. 4 (Oral), H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Not expected to require first aid measures.
First-aid measures after skin contact : Wash skin with mild soap and water.
First-aid measures after eye contact : In case of eye contact, immediately rinse with clean water for 10-15 minutes.
First-aid measures after ingestion : Do not induce vomiting. Rinse mouth. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact : Not expected to present a significant skin hazard under anticipated conditions of normal use.
Symptoms/effects after eye contact : Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
Symptoms/effects after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water fog. Foam. Powder. Dry chemical product.
Unsuitable extinguishing media : Do not use a heavy water stream.

Nordlub Kompressorenöl VDL 150

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Precautionary measures fire : Exercise caution when fighting any chemical fire.
Firefighting instructions : Use water spray or fog for cooling exposed containers.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Wear suitable protective clothing and gloves.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing and gloves.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Impound and recover large spill by mixing it with inert granular solids.
Methods for cleaning up : Detergent. Take up liquid spill into absorbent material sand, saw dust, kieselguhr.
Other information : Spill area may be slippery. Use suitable disposal containers.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid all unnecessary exposure. Both local exhaust and general room ventilation are usually required.
Handling temperature : < 40 °C
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage temperature : < 40 °C
Storage area : Store in dry, cool, well-ventilated area.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Naphthalene (91-20-3)

EU - Occupational Exposure Limits

IOELV TWA (ppm)	10 ppm
IOELV STEL (mg/m ³)	15 mg/m ³

Nordlub Kompressorenöl VDL 150

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Naphthalene (91-20-3)	
Austria - Occupational Exposure Limits	
MAK Daily average value (mg/m ³)	50 mg/m ³
Belgium - Occupational Exposure Limits	
Limit value (mg/m ³)	50 mg/m ³
Short time value (mg/m ³)	53 mg/m ³
Bulgaria - Occupational Exposure Limits	
OEL TWA (mg/m ³)	50 mg/m ³ 8h
OEL STEL (mg/m ³)	75 mg/m ³ 15 min.
Denmark - Occupational Exposure Limits	
<tx:_GRAENSEVAERDI> (STEL) (mg/m ³)	50 mg/m ³
Estonia - Occupational Exposure Limits	
OEL TWA (mg/m ³)	50 mg/m ³
Finland - Occupational Exposure Limits	
HTP-arvo (8h) (mg/m ³)	5 mg/m ³
HTP-arvo (15 min)	100 mg/m ³
France - Occupational Exposure Limits	
VME (mg/m ³)	50 mg/m ³
Germany - Occupational Exposure Limits (TRGS 900)	
Occupational exposure limit value (mg/m ³)	50 mg/m ³
Netherlands - Occupational Exposure Limits	
Grenswaarde TGG 8H (mg/m ³)	50 mg/m ³
Grenswaarde TGG 15MIN (mg/m ³)	80 mg/m ³
United Kingdom - Occupational Exposure Limits	
WEL TWA (mg/m ³)	50 mg/m ³
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (mg/m ³)	10 mg/m ³
ACGIH STEL (mg/m ³)	15 fibers/cm ³

Additional information : 5 mg/m³ for oil mists (TWA, 8h-workday) recommended, based upon the ACGIH TLV (Analysis according to US NIOSH Method 5026, NIOSH Manual of Analytical Methods, 3rd Edition).

8.2. Exposure controls

Personal protective equipment:

Safety glasses. Gloves.

Hand protection:

Permeation time: minimum >480min long term exposure; material / thickness [mm]: >0,35 mm. Nitrile rubber (NBR) /

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use

Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation.

Nordlub Kompressorenöl VDL 150

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Oily liquid.
Colour	: Yellow-brown.
Odour	: Characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 210 °C @ ASTM D92
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 895 kg/m ³ @ 15°C
Solubility	: Slightly soluble, the product remains on the water surface.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 150 mm ² /s @ 40°C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal conditions.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None under normal conditions.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

Strong oxidizers. acids. Bases.

10.6. Hazardous decomposition products

None under normal conditions.

Nordlub Kompressorenöl VDL 150

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Naphthalene (91-20-3)

LD50 oral rat	2600 mg/kg
LD50 dermal rat	> 2500 mg/kg

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Nordlub Kompressorenöl VDL 150

Viscosity, kinematic	150 mm ² /s @ 40°C
----------------------	-------------------------------

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Naphthalene (91-20-3)

LC50 fish 1	< 10 mg/l 96h
LC50 fish 2	0,51 mg/kg
LC50 other aquatic organisms 1	48h, Daphnia
EC50 Daphnia 1	3,4 mg/l
EC50 Daphnia 2	< 10 mg/l

Solvent naphtha (petroleum), heavy aromatic (64742-94-5)

LC50 fish 1	19 mg/l @Pimephales promelas static
LC50 fish 2	45 mg/l @pimephales promelas flow through
EC50 Daphnia 1	0,95 mg/l @ Daphnia magna
EC50 72h algae (1)	2,5 mg/l @Skeletonema Costatum

Nordlub Kompressorenöl VDL 150

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.2. Persistence and degradability

Nordlub Kompressorenöl VDL 150

Persistence and degradability	Not soluble in water, so only minimally biodegradable.
-------------------------------	--

Naphthalene (91-20-3)

Persistence and degradability	Inherently biodegradable.
-------------------------------	---------------------------

12.3. Bioaccumulative potential

Solvent naphtha (petroleum), heavy aromatic (64742-94-5)

Partition coefficient n-octanol/water (Log Pow)	2,9 – 6,1
---	-----------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Additional information : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: Not applicable
UN-No. (IMDG)	: Not applicable
UN-No. (IATA)	: Not applicable
UN-No. (ADN)	: Not applicable
UN-No. (RID)	: Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: Not applicable
Proper Shipping Name (IMDG)	: Not applicable
Proper Shipping Name (IATA)	: Not applicable
Proper Shipping Name (ADN)	: Not applicable
Proper Shipping Name (RID)	: Not applicable

14.3. Transport hazard class(es)

ADR
Transport hazard class(es) (ADR) : Not applicable

IMDG
Transport hazard class(es) (IMDG) : Not applicable

IATA
Transport hazard class(es) (IATA) : Not applicable

ADN
Transport hazard class(es) (ADN) : Not applicable

Nordlub Kompressorenöl VDL 150

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable
Packing group (ADN) : Not applicable
Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

No data available

Transport by sea

No data available

Air transport

No data available

Inland waterway transport

No data available

Rail transport

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

Germany

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : Solvent naphtha (petroleum), heavy aromatic is listed

SZW-lijst van mutagene stoffen : Solvent naphtha (petroleum), heavy aromatic is listed

NIET-limitatieve lijst van voor de voortplanting : None of the components are listed

giftige stoffen – Borstvoeding

NIET-limitatieve lijst van voor de voortplanting : None of the components are listed

giftige stoffen – Vruchtbaarheid

NIET-limitatieve lijst van voor de voortplanting : None of the components are listed

giftige stoffen – Ontwikkeling

Nordlub Kompressorenöl VDL 150

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Denmark

Danish National Regulations

: Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out for the substance or the mixture by the supplier

SECTION 16: Other information

Indication of changes:			
Section	Changed item	Change	Comments
	Revision date	Modified	
	Supersedes	Modified	
	SDS EU format	Modified	
3	Composition/information on ingredients	Modified	

Abbreviations and acronyms:

	ACGIH: American Conference of Governmental Industrial Hygienists
	TWA: Time Weighted Average
	TLV: Threshold Limit Value
	ASTM: American Society for Testing and Materials
	ADR: Accord Européen Relatif au Transport International des Marchandises Dangereuses par Route
	RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
	ADNR: Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin
	IMDG: International Maritime Dangerous Goods
	ICAO: International Civil Aviation Organization
	IATA: International Air Transport Association
	STEL: Short Term Exposure Limit
	LD50: median Lethal Dose for 50% of subjects
	ATE: acute toxicity estimate
	LC50: median Lethal Concentration for 50% of subjects
	EC50: concentration producing 50% effect

Other information

: The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1

Nordlub Kompressorenöl VDL 150

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Aryl amine. May produce an allergic reaction.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.